

### TEMPLATE SPRING HINGES

SINGLE ACTING, FULL MORTISE, NON-HANDED



#### FEATURES



- UL & ULC listed for fire door applications
- Made in U.S.A.
- Steel material
- Easily adjusted spring tension
- Screw hole pattern conforms to ANSI 4310, 4311, 4312 (ANSI K81071F)
- Pivot point aligns with hinges of same size

#### USES

- Minimizes cost of installing a door closing device on industrial, commercial, institutional and residential applications
- Use to convert doors to self-closing in existing buildings
- For use in hotels, motels, apartments, dormitories, residences, etc., where doors are required to be self-closing (always verify local fire code requirements)

#### Hinge Selection Chart

4300 Series	Max. Door Weight (lb)	Spring Hinges (pcs.)	Butt Hinges (pcs.)
3-1/2" x 3-1/2"	50	2	1
	70	2	1
	90	3	-
4" x 4"	60	2	1
	85	2	1
	110	3	-
4-1/2" x 4" (4-1/2")	70	2	1
	115	2	1
	150	3	-

MODEL No.	SIZE	CORNERS	FINISH	 ea	 Kg
4310	3-1/2" x 3-1/2"	Square	C10, C26D, C2G, C3, C4, CP	40	13.0
4310	4" x 4"	Square	C10, C15, C26D, C2G, C3, C4, CP	40	15.0
4310	4-1/2" x 4"	Square	BLR, C10, C15, C26D, C2G, C3, C4, CP	40	20.0
4310	4-1/2" x 4-1/2"	Square	C2G, C3, C4, CP	40	21.0
4311	3-1/2" x 3-1/2"	1/4" Radius	C26D, C2G, C4	40	13.0
4311	4" x 4"	1/4" Radius	C10, C15A, C2G, C4, CP	40	15.0
4312	3-1/2" x 3-1/2"	5/8" Radius	C26D, C4	40	13.0
	4" x 4"		C4	40	15.0
4361	4" x 4"	5/8" Radius / Square	C2G	40	15.0

